

RABOESCH®

RC Model Boat Accessories *Im Vertrieb von
Klaus Krick
Modelltechnik*



2020



GB At Raboesch Models we have been, enthusiastically, creating model ship building products for more than 36 years. High-quality products, precise tools and professionalism result in top quality-products. Through a global network of distributors and dealers our products end up in the hands of the hobbyist. Also outside of the model building sector companies discover the high and constant quality of the Raboesch products. Our products are being used, more and more lately, in the high-tech industry, such as in robotics, various research & development departments and government institutions.

In front of you lies the Raboesch catalog with all the new as well as the more trusted classic products. We wish you plenty of enjoyment while perusing our offers and we invite you to allow yourself to be inspired at one of our retail outlets. On our website: www.raboeschmodels.com you will find an up-to-date overview of all our products and activities.

NL Al ruim 36 jaar worden er bij Raboesch Models, met enthousiasme, producten vervaardigd voor de scheepsmodebouw. Hoogwaardige materialen, precisie gereedschap en vakmanschap resulteren in producten van topkwaliteit. Via een wereldwijd netwerk van distributeurs en dealers komen de producten terecht bij de hobbyist. Ook buiten de modelbouwbranche ontdekken bedrijven de hoge en constante kwaliteit van Raboesch producten. Onze producten worden steeds meer gebruikt in de hightech industrie, zoals in robotica, diverse research & development afdelingen en overheidsinstellingen.

Voor u ligt de Raboesch catalogus met nieuwe en vertrouwde producten. We wensen u veel plezier bij het bekijken van ons aanbod en nodigen u uit om u te laten inspireren bij een van onze verkooppunten. Op onze website: www.raboeschmodels.com vindt u een actueel overzicht van onze producten en activiteiten.

DE Schon seit mehr als 36 Jahren werden bei Raboesch Models, mit Begeisterung Produkte für den Schiffsmodellbau hergestellt. Hochwertige Materialien, Präzisionsgeräte sowie fachmännisches Können erzeugen Produkte in Spitzenqualität. Über ein weltweites Händler- und Verteilernetzwerk gelangen die Produkte beim Hobbyisten. Auch außerhalb der Modellbaubranche entdecken Firmen die hohe und gleichbleibende Qualität der Raboesch Produkte. Unsere Produkte werden immer häufiger in der Hightech Industrie verwendet, zum Beispiel für Robotik-Systeme, in verschiedenen Forschungs- und Entwicklungsabteilungen und bei Behördeninstanzen.

Vor Ihnen liegt jetzt der Raboesch Katalog mit neuen und vertrauten Produkten. Wir wünschen Ihnen viel Freude beim Stöbern durch unser Angebot und laden Sie ein, sich von einer unserer Verkaufsstellen begeistern und inspirieren zu lassen. Auf unserer Website: www.raboeschmodels.com finden Sie eine aktuelle Übersicht unserer Produkte und Aktivitäten.

FR Depuis plus de 36 ans, chez Raboesch Models, avec enthousiasme, on fabrique des produits pour le modélisme naval. Les matériaux de haute qualité, les outils de précision et l'artisanat résultent en des produits de haute qualité. Grâce à un réseau mondial de distributeurs et de revendeurs, les produits arrivent chez les amateurs. Egalement en dehors du secteur d'activité de la construction de maquettes, les entreprises découvrent la qualité élevée et constante des produits Raboesch. Nos produits sont de plus en plus utilisés dans les industries de haute technologie, telles que la robotique, les divers départements de recherche et développement et les organismes gouvernementaux.

Vous avez devant vous le catalogue de Raboesch avec des produits nouveaux et dignes de confiance. Nous vous souhaitons beaucoup de plaisir avec la considération de notre offre et vous invitons à vous laisser inspirer par un de nos points de vente. Sur notre site web: www.raboeschmodels.com vous trouverez un aperçu de nos produits et de nos activités.

Rotation direction of propellers

Draairichting van schepsschroeven – Drehrichtung Schiffsschrauben – Direction hélices


GB In the illustration given below you can see the propellers according to International Standard. All Raboesch Models BV propellers are made according to International Standard

NL In de onderstaande illustratie ziet u de schroeven afgebeeld volgens de Internationale Standaard. Alle schroeven van Raboesch Models BV worden geleverd volgens de Internationale standaard.

DE In der nachstehenden Zeichnung sind die Schrauben abgebildet nach dem Internationalen Standard. Alle Raboesch Models BV Propeller werden nach Internationalem Standard hergestellt.

FR Dans l'illustration ci-dessous, vous voyez les hélices représentées pour vous selon la Norme Internationale. Toutes les hélices de Raboesch Models BV sont fabriquées selon la Norme Internationale.

Rotation direction of Raboesch propellers



Brass propellers

Messing sloopsschroeven - Messing Schiffsschrauben - Hélices laiton




145 / A-type



145 - 2 blade METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
145-41	20	0,79	R	M2	20,5	6 x 10 mm	16000
145-42	20	0,79	L	M2	20,5	6 x 10 mm	16000
145-43	20	0,79	R	M3	20,5	6 x 10 mm	16000
145-44	20	0,79	L	M3	20,5	6 x 10 mm	16000
145-45	25	0,98	R	M2	25,6	7 x 12 mm	16000
145-46	25	0,98	L	M2	25,6	7 x 12 mm	16000
145-47	25	0,98	R	M3	25,6	7 x 12 mm	16000
145-48	25	0,98	L	M3	25,6	7 x 12 mm	16000
145-49	25	0,98	R	M4	25,6	7 x 12 mm	16000
145-50	25	0,98	L	M4	25,6	7 x 12 mm	16000
145-01	30	1,20	R	M4	30,7	8 x 14,5 mm	14500
145-02	30	1,20	L	M4	30,7	8 x 14,5 mm	14500
145-01A	30	1,20	R	M3	30,7	8 x 14,5 mm	14500
145-02A	30	1,20	L	M3	30,7	8 x 14,5 mm	14500
145-03	35	1,40	R	M4	35,9	8 x 14,5 mm	14500
145-04	35	1,40	L	M4	35,9	8 x 14,5 mm	14500
145-03A	35	1,40	R	M3	35,9	8 x 14,5 mm	14500
145-04A	35	1,40	L	M3	35,9	8 x 14,5 mm	14500
145-05	40	1,60	R	M4	41,0	9 x 16 mm	13000
145-06	40	1,60	L	M4	41,0	9 x 16 mm	13000
145-07	45	1,80	R	M4	46,1	9 x 16 mm	12000
145-08	45	1,80	L	M4	46,1	9 x 16 mm	12000
145-09	50	2,00	R	M4	51,2	10 x 18 mm	10000
145-10	50	2,00	L	M4	51,2	10 x 18 mm	10000
145-11	60	2,40	R	M4	61,5	11 x 22 mm	8000
145-12	60	2,40	L	M4	61,5	11 x 22 mm	8000
145-13	60	2,40	R	M5	61,5	11 x 22 mm	8000
145-14	60	2,40	L	M5	61,5	11 x 22 mm	8000



146 / A-type




146 - 3 blade METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
146-01	20	0,79	R	M3	20,5	6 x 10 mm	16000
146-02	20	0,79	L	M3	20,5	6 x 10 mm	16000
146-01A	20	0,79	R	M2	20,5	6 x 10 mm	16000
146-02A	20	0,79	L	M2	20,5	6 x 10 mm	16000
146-05	20	0,79	R	M4	20,5	6 x 10 mm	16000
146-06	20	0,79	L	M4	20,5	6 x 10 mm	16000
146-03	25	0,98	R	M3	25,6	7 x 12 mm	16000
146-04	25	0,98	L	M3	25,6	7 x 12 mm	16000
146-03A	25	0,98	R	M2	25,6	7 x 12 mm	16000

146 - 3 blade METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
146-04A	25	0,98	L	M2	25,6	7 x 12 mm	16000
146-07	25	0,98	R	M4	25,6	7 x 12 mm	16000
146-08	25	0,98	L	M4	25,6	7 x 12 mm	16000
146-09	30	1,20	R	M4	30,7	8 x 14,5 mm	14500
146-10	30	1,20	L	M4	30,7	8 x 14,5 mm	14500
146-09A	30	1,20	R	M3	30,7	8 x 14,5 mm	14500
146-10A	30	1,20	L	M3	30,7	8 x 14,5 mm	14500
146-11	35	1,40	R	M4	35,9	8 x 14,5 mm	14500
146-12	35	1,40	L	M4	35,9	8 x 14,5 mm	14500
146-11A	35	1,40	R	M3	35,9	8 x 14,5 mm	14500
146-12A	35	1,40	L	M3	35,9	8 x 14,5 mm	14500
146-13	40	1,60	R	M4	41,0	9 x 16 mm	13000
146-14	40	1,60	L	M4	41,0	9 x 16 mm	13000
146-15	45	1,80	R	M4	46,1	9 x 16 mm	12000
146-16	45	1,80	L	M4	46,1	9 x 16 mm	12000
146-17	50	2,00	R	M4	51,2	10 x 18 mm	10000
146-18	50	2,00	L	M4	51,2	10 x 18 mm	10000
146-19	55	2,20	R	M4	56,4	10 x 18 mm	9600
146-20	55	2,20	L	M4	56,4	10 x 18 mm	9600
146-21	60	2,40	R	M4	61,5	11 x 22 mm	8000
146-22	60	2,40	L	M4	61,5	11 x 22 mm	8000
146-21A	60	2,40	R	M5	61,5	11 x 22 mm	8000
146-22A	60	2,40	L	M5	61,5	11 x 22 mm	8000
146-23	65	2,60	R	M4	66,6	11 x 22 mm	6600
146-24	65	2,60	L	M4	66,6	11 x 22 mm	6600
146-23A	65	2,60	R	M5	66,6	11 x 22 mm	6600
146-24A	65	2,60	L	M5	66,6	11 x 22 mm	6600
146-25	70	2,80	R	M5	71,7	12 x 24 mm	6200
146-26	70	2,80	L	M5	71,7	12 x 24 mm	6200
146-25A	70	2,80	R	M4	71,7	12 x 24 mm	6200
146-26A	70	2,80	L	M4	71,7	12 x 24 mm	6200
146-27	75	3,00	R	M5	76,9	12 x 24 mm	4200
146-28	75	3,00	L	M5	76,9	12 x 24 mm	4200
146-27A	75	3,00	R	M4	76,9	12 x 24 mm	4200
146-28A	75	3,00	L	M4	76,9	12 x 24 mm	4200
146-29	80	3,20	R	M5	82,0	13 x 26 mm	3500
146-30	80	3,20	L	M5	82,0	13 x 26 mm	3500
146-31	90	3,60	R	M5	92,2	14 x 28 mm	3100
146-32	90	3,60	L	M5	92,2	14 x 28 mm	3100
146-33	100	4,00	R	M5	102,5	15 x 30 mm	2800
146-34	100	4,00	L	M5	102,5	15 x 30 mm	2800
146-35	110	4,40	R	M5	112,8	16 x 32 mm	2500
146-36	110	4,40	L	M5	112,8	16 x 32 mm	2500
146-39	120	4,70	R	M5	123,0	18 x 36 mm	2300
146-40	120	4,70	L	M5	123,0	18 x 36 mm	2300
146-37	130	5,10	R	M5	133,2	20 x 40 mm	2150
146-38	130	5,10	L	M5	133,2	20 x 40 mm	2150



147 / A-type



147 - 4 blade METRIC shaft connection

Brass propellers

Messing sloopsschroeven - Messing Schiffsschrauben - Hélices laiton



147 - 4 blade

METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
147-01	20	0,79	R	M3	20,5	6 x 10 mm	16000
147-02	20	0,79	L	M3	20,5	6 x 10 mm	16000
147-01A	20	0,79	R	M2	20,5	6 x 10 mm	16000
147-02A	20	0,79	L	M2	20,5	6 x 10 mm	16000
147-05	20	0,79	R	M4	20,5	6 x 10 mm	16000
147-06	20	0,79	L	M4	20,5	6 x 10 mm	16000
147-03	25	0,98	R	M3	25,6	7 x 12 mm	16000
147-04	25	0,98	L	M3	25,6	7 x 12 mm	16000
147-03A	25	0,98	R	M2	25,6	7 x 12 mm	16000
147-04A	25	0,98	L	M2	25,6	7 x 12 mm	16000
147-07	25	0,98	R	M4	25,6	7 x 12 mm	16000
147-08	25	0,98	L	M4	25,6	7 x 12 mm	16000
147-09	30	1,20	R	M4	30,7	8 x 14,5 mm	14500
147-10	30	1,20	L	M4	30,7	8 x 14,5 mm	14500
147-09A	30	1,20	R	M3	30,7	8 x 14,5 mm	14500
147-10A	30	1,20	L	M3	30,7	8 x 14,5 mm	14500
147-11	35	1,40	R	M4	35,9	8 x 14,5 mm	14500
147-12	35	1,40	L	M4	35,9	8 x 14,5 mm	14500
147-11A	35	1,40	R	M3	35,9	8 x 14,5 mm	14500
147-12A	35	1,40	L	M3	35,9	8 x 14,5 mm	14500
147-13	40	1,60	R	M4	41,0	9 x 16 mm	13000
147-14	40	1,60	L	M4	41,0	9 x 16 mm	13000
147-15	45	1,80	R	M4	46,1	9 x 16 mm	12000
147-16	45	1,80	L	M4	46,1	9 x 16 mm	12000
147-17	50	2,00	R	M4	51,2	10 x 18 mm	10000
147-18	50	2,00	L	M4	51,2	10 x 18 mm	10000
147-19	55	2,20	R	M4	56,4	10 x 18 mm	9600
147-20	55	2,20	L	M4	56,4	10 x 18 mm	9600
147-21	60	2,40	R	M4	61,5	11 x 22 mm	8000
147-22	60	2,40	L	M4	61,5	11 x 22 mm	8000
147-21A	60	2,40	R	M5	61,5	11 x 22 mm	8000
147-22A	60	2,40	L	M5	61,5	11 x 22 mm	8000
147-23	65	2,60	R	M4	66,6	11 x 22 mm	6600
147-24	65	2,60	L	M4	66,6	11 x 22 mm	6600
147-23A	65	2,60	R	M5	66,6	11 x 22 mm	6600
147-24A	65	2,60	L	M5	66,6	11 x 22 mm	6600
147-25	70	2,80	R	M5	71,7	12 x 24 mm	6200
147-26	70	2,80	L	M5	71,7	12 x 24 mm	6200
147-25A	70	2,80	R	M4	71,7	12 x 24 mm	6200
147-26A	70	2,80	L	M4	71,7	12 x 24 mm	6200
147-27	75	3,00	R	M5	76,9	12 x 24 mm	4200
147-28	75	3,00	L	M5	76,9	12 x 24 mm	4200
147-27A	75	3,00	R	M4	76,9	12 x 24 mm	4200
147-28A	75	3,00	L	M4	76,9	12 x 24 mm	4200
147-29	80	3,20	R	M5	82,0	13 x 26 mm	3500
147-30	80	3,20	L	M5	82,0	13 x 26 mm	3500
147-31	90	3,60	R	M5	92,2	14 x 28 mm	3100
147-32	90	3,60	L	M5	92,2	14 x 28 mm	3100
147-33	100	4,00	R	M5	102,5	15 x 30 mm	2800
147-34	100	4,00	L	M5	102,5	15 x 30 mm	2800
147-35	110	4,40	R	M5	112,8	16 x 32 mm	2500
147-36	110	4,40	L	M5	112,8	16 x 32 mm	2500
147-39	120	4,70	R	M5	123,0	18 x 36 mm	2300
147-40	120	4,70	L	M5	123,0	18 x 36 mm	2300
147-37	130	5,10	R	M5	133,2	20 x 40 mm	2150
147-38	130	5,10	L	M5	133,2	20 x 40 mm	2150



148 / A-type



148 - 5 blade

METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
148-41	20	0,79	R	M2	20,5	6 x 10 mm	16000
148-42	20	0,79	L	M2	20,5	6 x 10 mm	16000
148-43	20	0,79	R	M3	20,5	6 x 10 mm	16000
148-44	20	0,79	L	M3	20,5	6 x 10 mm	16000
148-45	25	0,98	R	M2	25,6	7 x 12 mm	16000
148-46	25	0,98	L	M2	25,6	7 x 12 mm	16000
148-47	25	0,98	R	M3	25,6	7 x 12 mm	16000
148-48	25	0,98	L	M3	25,6	7 x 12 mm	16000
148-49	25	0,98	R	M4	25,6	7 x 12 mm	16000
148-50	25	0,98	L	M4	25,6	7 x 12 mm	16000
148-01	30	1,20	R	M4	30,7	8 x 14,5 mm	14500
148-02	30	1,20	L	M4	30,7	8 x 14,5 mm	14500
148 01A	30	1,20	R	M3	30,7	8 x 14,5 mm	14500
148-02A	30	1,20	L	M3	30,7	8 x 14,5 mm	14500
148-03	35	1,40	R	M4	35,9	8 x 14,5 mm	14500
148-04	35	1,40	L	M4	35,9	8 x 14,5 mm	14500
148-03A	35	1,40	R	M3	35,9	8 x 14,5 mm	14500
148-04A	35	1,40	L	M3	35,9	8 x 14,5 mm	14500
148-05	40	1,60	R	M4	41,0	9 x 16 mm	13000
148-06	40	1,60	L	M4	41,0	9 x 16 mm	13000
148-07	45	1,80	R	M4	46,1	9 x 16 mm	12000
148-08	45	1,80	L	M4	46,1	9 x 16 mm	12000
148-09	50	2,00	R	M4	51,2	10 x 18 mm	10000
148-10	50	2,00	L	M4	51,2	10 x 18 mm	10000
148-11	55	2,20	R	M4	56,4	10 x 18 mm	9600
148-12	55	2,20	L	M4	56,4	10 x 18 mm	9600
148-13	60	2,40	R	M4	61,5	11 x 22 mm	8000
148-14	60	2,40	L	M4	61,5	11 x 22 mm	8000
148-13A	60	2,40	R	M5	61,5	11 x 22 mm	8000
148-14A	60	2,40	L	M5	61,5	11 x 22 mm	8000
148-15	65	2,60	R	M4	66,6	11 x 22 mm	6600
148-16	65	2,60	L	M4	66,6	11 x 22 mm	6600
148-15A	65	2,60	R	M5	66,6	11 x 22 mm	6600
148-16A	65	2,60	L	M5	66,6	11 x 22 mm	6600
148-17	70	2,80	R	M4	71,7	12 x 24 mm	6200
148-18	70	2,80	L	M4	71,7	12 x 24 mm	6200
148-17A	70	2,80	R	M5	71,7	12 x 24 mm	6200
148-18A	70	2,80	L	M5	71,7	12 x 24 mm	6200
148-19	75	3,00	R	M5	76,9	12 x 24 mm	4200
148-20	75	3,00	L	M5	76,9	12 x 24 mm	4200
148-21	80	3,20	R	M5	82,0	13 x 26 mm	3500
148-22	80	3,20	L	M5	82,0	13 x 26 mm	3500
148-23	90	3,60	R	M5	92,2	14 x 28 mm	3100
148-24	90	3,60	L	M5	92,2	14 x 28 mm	3100
148-25	100	4,00	R	M5	102,5	15 x 30 mm	2800
148-26	100	4,00	L	M5	102,5	15 x 30 mm	2800
148-27	110	4,40	R	M5	112,8	16 x 32 mm	2500
148-28	110	4,40	L	M5	112,8	16 x 32 mm	2500
148-29	120	4,70	R	M5	123,0	18 x 36 mm	2300
148-30	120	4,70	L	M5	123,0	18 x 36 mm	2300
148-31	130	5,10	R	M5	133,2	20 x 40 mm	2150
148-32	130	5,10	L	M5	133,2	20 x 40 mm	2150

Brass propellers

Messing sloopsschroeven - Messing Schiffsschrauben - Hélices laiton



hobby products



149 / A-type



149 - 4 blade

METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
149-01	30	1,20	R	M4	30,7	8 x 14,5 mm	14500
149-02	30	1,20	L	M4	30,7	8 x 14,5 mm	14500
149-01A	30	1,20	R	M3	30,7	8 x 14,5 mm	14500
149-02A	30	1,20	L	M3	30,7	8 x 14,5 mm	14500
149-03	35	1,40	R	M4	35,9	9 x 16 mm	14500
149-04	35	1,40	L	M4	35,9	9 x 16 mm	14500
149-05	40	1,60	R	M4	41,0	10 x 18 mm	13000
149-06	40	1,60	L	M4	41,0	10 x 18 mm	13000
149-07	45	1,80	R	M4	46,1	10 x 18 mm	12000
149-08	45	1,80	L	M4	46,1	10 x 18 mm	12000
149-09	50	2,00	R	M4	51,2	11 x 22 mm	10000
149-10	50	2,00	L	M4	51,2	11 x 22 mm	10000
149-65	55	2,20	R	M4	56,4	11 x 22 mm	9600
149-66	55	2,20	L	M4	56,4	11 x 22 mm	9600
149-67	55	2,20	R	M5	56,4	11 x 22 mm	9600
149-68	55	2,20	L	M5	56,4	11 x 22 mm	9600
149-11	60	2,40	R	M5	61,5	12 x 24 mm	8000
149-12	60	2,40	L	M5	61,5	14 x 24 mm	8000
149-11A	60	2,40	R	M4	61,5	13 x 24 mm	8000
149-12A	60	2,40	L	M4	61,5	15 x 24 mm	8000
149-13	70	2,80	R	M5	71,7	13 x 26 mm	6200
149-14	70	2,80	L	M5	71,7	13 x 26 mm	6200
149-15	80	3,20	R	M5	82,0	15 x 30 mm	3500
149-16	80	3,20	L	M5	82,0	15 x 30 mm	3500
149-17	90	3,60	R	M5	92,2	16 x 32 mm	3100
149-18	90	3,60	L	M5	92,2	16 x 32 mm	3100
149-19	100	4,00	R	M5	102,5	18 x 36 mm	2800
149-20	100	4,00	L	M5	102,5	18 x 36 mm	2800
149-21	110	4,40	R	M5	112,8	20 x 40 mm	2500
149-22	110	4,40	L	M5	112,8	20 x 40 mm	2500

NIEUW - NEW - NEU - NOUVEAUTE - 2020



150 / A-type



150 - 3 blade

METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
150-01	30	1,20	R	M3	30,7	8 x 14,5 mm	14500
150-02	30	1,20	L	M3	30,7	8 x 14,5 mm	14500
150-03	30	1,20	R	M4	30,7	8 x 14,5 mm	14500
150-04	30	1,20	L	M4	30,7	8 x 14,5 mm	14500
150-05	35	1,40	R	M4	35,9	9 x 16 mm	14500
150-06	35	1,40	L	M4	35,9	9 x 16 mm	14500
150-07	40	1,60	R	M4	41,0	10 x 18 mm	13000
150-08	40	1,60	L	M4	41,0	10 x 18 mm	13000
150-09	45	1,80	R	M4	46,1	10 x 18 mm	12000

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
150-10	45	1,80	L	M4	46,1	10 x 18 mm	12000
150-11	50	2,00	R	M4	51,2	11 x 22 mm	10000
150-12	50	2,00	L	M4	51,2	11 x 22 mm	10000
150-65	55	2,20	R	M4	56,4	11 x 22 mm	9600
150-66	55	2,20	L	M4	56,4	11 x 22 mm	9600
150-67	55	2,20	R	M5	56,4	11 x 22 mm	9600
150-68	55	2,20	L	M5	56,4	11 x 22 mm	9600
150-13	60	2,40	R	M4	61,5	12 x 24 mm	8000
150-14	60	2,40	L	M4	61,5	12 x 24 mm	8000
150-15	60	2,40	R	M5	61,5	12 x 24 mm	8000
150-16	60	2,40	L	M5	61,5	12 x 24 mm	8000
150-17	70	2,80	R	M5	71,7	13 x 26 mm	6200
150-18	70	2,80	L	M5	71,7	13 x 26 mm	6200
150-19	80	3,20	R	M5	82,0	15 x 30 mm	3500
150-20	80	3,20	L	M5	82,0	15 x 30 mm	3500
150-21	90	3,60	R	M5	92,2	16 x 32 mm	3100
150-22	90	3,60	L	M5	92,2	16 x 32 mm	3100
150-23	100	4,00	R	M5	102,5	18 x 36 mm	2800
150-24	100	4,00	L	M5	102,5	18 x 36 mm	2800
150-25	110	4,40	R	M5	112,8	20 x 40 mm	2500
150-26	110	4,40	L	M5	112,8	20 x 40 mm	2500

NIEUW - NEW - NEU - NOUVEAUTE - 2020



151 / A-type



151 - 5 blade

METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
151-01	30	1,20	R	M3	30,7	8 x 14,5 mm	14500
151-02	30	1,20	L	M3	30,7	8 x 14,5 mm	14500
151-03	30	1,20	R	M4	30,7	8 x 14,5 mm	14500
151-04	30	1,20	L	M4	30,7	8 x 14,5 mm	14500
151-05	35	1,40	R	M4	35,9	9 x 16 mm	14500
151-06	35	1,40	L	M4	35,9	9 x 16 mm	14500
151-07	40	1,60	R	M4	41,0	10 x 18 mm	13000
151-08	40	1,60	L	M4	41,0	10 x 18 mm	13000
151-09	45	1,80	R	M4	46,1	10 x 18 mm	12000
151-10	45	1,80	L	M4	46,1	10 x 18 mm	12000
151-11	50	2,00	R	M4	51,2	11 x 22 mm	10000
151-12	50	2,00	L	M4	51,2	11 x 22 mm	10000
151-65	55	2,20	R	M4	56,4	11 x 22 mm	9600
151-66	55	2,20	L	M4	56,4	11 x 22 mm	9600
151-67	55	2,20	R	M5	56,4	11 x 22 mm	9600
151-68	55	2,20	L	M5	56,4	11 x 22 mm	9600
151-13	60	2,40	R	M4	61,5	12 x 24 mm	8000
151-14	60	2,40	L	M4	61,5	12 x 24 mm	8000
151-15	60	2,40	R	M5	61,5	12 x 24 mm	8000
151-16	60	2,40	L	M5	61,5	12 x 24 mm	8000
151-17	70	2,80	R	M5	71,7	13 x 26 mm	6200
151-18	70	2,80	L	M5	71,7	13 x 26 mm	6200
151-19	80	3,20	R	M5	82,0	15 x 30 mm	3500
151-20	80	3,20	L	M5	82,0	15 x 30 mm	3500
151-21	90	3,60	R	M5	92,2	16 x 32 mm	3100
151-22	90	3,60	L	M5	92,2	16 x 32 mm	3100
151-23	100	4,00	R	M5	102,5	18 x 36 mm	2800
151-24	100	4,00	L	M5	102,5	18 x 36 mm	2800
151-25	110	4,40	R	M5	112,8	20 x 40 mm	2500
151-26	110	4,40	L	M5	112,8	20 x 40 mm	2500

NIEUW - NEW - NEU - NOUVEAUTE - 2020

Brass propellers

Messing sloopsschroeven - Messing Schiffsschrauben - Hélices laiton



154 / C-type



154 - 2 blade METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
154-41	20	0,79	R	M2	20,5	6 x 10 mm	16000
154-42	20	0,79	L	M2	20,5	6 x 10 mm	16000
154-43	20	0,79	R	M3	20,5	6 x 10 mm	16000
154-44	20	0,79	L	M3	20,5	6 x 10 mm	16000
154-45	25	0,98	R	M2	25,6	7 x 12 mm	16000
154-46	25	0,98	L	M2	25,6	7 x 12 mm	16000
154-47	25	0,98	R	M3	25,6	7 x 12 mm	16000
154-48	25	0,98	L	M3	25,6	7 x 12 mm	16000
154-49	25	0,98	R	M4	25,6	7 x 12 mm	16000
154-50	25	0,98	L	M4	25,6	7 x 12 mm	16000
154-01	30	1,20	R	M3	26,7	8 x 14,5 mm	14500
154-02	30	1,20	L	M3	26,7	8 x 14,5 mm	14500
154-01A	30	1,20	R	M4	26,7	8 x 14,5 mm	14500
154-02A	30	1,20	L	M4	26,7	8 x 14,5 mm	14500
154-03	35	1,40	R	M3	31,1	8 x 14,5 mm	14500
154-04	35	1,40	L	M3	31,1	8 x 14,5 mm	14500
154-03A	35	1,40	R	M4	31,1	8 x 14,5 mm	14500
154-04A	35	1,40	L	M4	31,1	8 x 14,5 mm	14500
154-05	40	1,60	R	M4	35,6	9 x 16 mm	13000
154-06	40	1,60	L	M4	35,6	9 x 16 mm	13000
154-07	45	1,80	R	M4	40,0	9 x 16 mm	12000
154-08	45	1,80	L	M4	40,0	9 x 16 mm	12000
154-09	50	2,00	R	M4	44,5	10 x 18 mm	10000
154-10	50	2,00	L	M4	44,5	10 x 18 mm	10000
154-11	55	2,20	R	M4	49,0	10 x 18 mm	9600
154-12	55	2,20	L	M4	49,0	10 x 18 mm	9600
154-13	60	2,40	R	M4	61,5	11 x 22 mm	8000
154-14	60	2,40	L	M4	61,5	11 x 22 mm	8000
154-15	60	2,40	R	M5	61,5	11 x 22 mm	8000
154-16	60	2,40	L	M5	61,5	11 x 22 mm	8000



156 / D-type



156 - 3 blade METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
156-41	20	0,79	R	M2	20,5	6 x 10 mm	16000
156-42	20	0,79	L	M2	20,5	6 x 10 mm	16000
156-43	20	0,79	R	M3	20,5	6 x 10 mm	16000
156-44	20	0,79	L	M3	20,5	6 x 10 mm	16000

156 - 3 blade METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
156-45	25	0,98	R	M2	25,6	7 x 12 mm	16000
156-46	25	0,98	L	M2	25,6	7 x 12 mm	16000
156-47	25	0,98	R	M3	25,6	7 x 12 mm	16000
156-48	25	0,98	L	M3	25,6	7 x 12 mm	16000
156-49	25	0,98	R	M4	25,6	7 x 12 mm	16000
156-50	25	0,98	L	M4	25,6	7 x 12 mm	16000
156-01	30	1,20	R	M4	26,7	8 x 14,5 mm	14500
156-02	30	1,20	L	M4	26,7	8 x 14,5 mm	14500
156-01A	30	1,20	R	M3	26,7	8 x 14,5 mm	14500
156-02A	30	1,20	L	M3	26,7	8 x 14,5 mm	14500
156-03	35	1,40	R	M4	31,1	8 x 14,5 mm	14500
156-04	35	1,40	L	M4	31,1	8 x 14,5 mm	14500
156-03A	35	1,40	R	M3	33,1	8 x 14,5 mm	14500
156-04A	35	1,40	L	M3	33,1	8 x 14,5 mm	14500
156-05	40	1,60	R	M4	35,6	9 x 16 mm	13000
156-06	40	1,60	L	M4	35,6	9 x 16 mm	13000
156-07	45	1,80	R	M4	40,0	9 x 16 mm	12000
156-08	45	1,80	L	M4	40,0	9 x 16 mm	12000
156-09	50	2,00	R	M4	44,5	10 x 18 mm	10000
156-10	50	2,00	L	M4	44,5	10 x 18 mm	10000
156-11	55	2,20	R	M4	49,0	10 x 18 mm	9600
156-12	55	2,20	L	M4	49,0	10 x 18 mm	9600
156-13	60	2,40	R	M4	53,3	11 x 22 mm	8000
156-14	60	2,40	L	M4	53,3	11 x 22 mm	8000
156-15	60	2,40	R	M5	53,3	11 x 22 mm	8000
156-16	60	2,40	L	M5	53,3	11 x 22 mm	8000



157 / D-type



157 - 3 blade INCH shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
157-01	30	1,20	R	3/16	26,7	8 x 14,5 mm	14500
157-02	30	1,20	L	3/16	26,7	8 x 14,5 mm	14500
157-03	35	1,40	R	3/16	31,1	8 x 14,5 mm	14500
157-04	35	1,40	L	3/16	31,1	8 x 14,5 mm	14500
157-05	40	1,60	R	3/16	35,6	9 x 16 mm	13000
157-06	40	1,60	L	3/16	35,6	9 x 16 mm	13000
157-07	45	1,80	R	3/16	40,0	9 x 16 mm	12000
157-08	45	1,80	L	3/16	40,0	9 x 16 mm	12000
157-09	50	2,00	R	3/16	44,5	10 x 18 mm	10000
157-10	50	2,00	L	3/16	44,5	10 x 18 mm	10000
157-11	55	2,20	R	3/16	49,0	10 x 18 mm	9600
157-12	55	2,20	L	3/16	49,0	10 x 18 mm	9600
157-13	60	2,40	R	3/16	53,3	11 x 22 mm	8000
157-14	60	2,40	L	3/16	53,3	11 x 22 mm	8000

Brass propellers

Messing sloopsschroeven - Messing Schiffsschrauben - Hélices laiton




158 / B-type



158 - 4 blade

METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
158-05	40	1,60	R	M4	41,0	9 x 16 mm	13000
158-06	40	1,60	L	M4	41,0	9 x 16 mm	13000
158-07	45	1,80	R	M4	46,1	9 x 16 mm	12000
158-08	45	1,80	L	M4	46,1	9 x 16 mm	12000
158-09	50	2,00	R	M4	51,2	10 x 18 mm	10000
158-10	50	2,00	L	M4	51,2	10 x 18 mm	10000
158-11	55	2,20	R	M4	56,4	10 x 18 mm	9600
158-12	55	2,20	L	M4	56,4	10 x 18 mm	9600
158-13	60	2,40	R	M4	61,5	11 x 22 mm	8000
158-14	60	2,40	L	M4	61,5	11 x 22 mm	8000
158-13A	60	2,40	R	M5	61,5	11 x 22 mm	8000
158-14A	60	2,40	L	M5	61,5	11 x 22 mm	8000
158-15	65	2,60	R	M4	66,6	11 x 22 mm	6600
158-16	65	2,60	L	M4	66,6	11 x 22 mm	6600
158-15A	65	2,60	R	M5	66,6	11 x 22 mm	6600
158-16A	65	2,60	L	M5	66,6	11 x 22 mm	6600
158-17	70	2,80	R	M4	71,7	12 x 24 mm	6200
158-18	70	2,80	L	M4	71,7	12 x 24 mm	6200
158-17A	70	2,80	R	M5	71,7	12 x 24 mm	6200
158-18A	70	2,80	L	M5	71,7	12 x 24 mm	6200



160 / C-type



160 - 3 blade


METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
160-41	20	0,79	R	M2	20,5	5 x 9	16000
160-42	20	0,79	L	M2	20,5	5 x 9	16000
160-43	20	0,79	R	M3	20,5	5 x 9	16000
160-44	20	0,79	L	M3	20,5	5 x 9	16000
160-45	25	0,98	R	M2	25,6	7 x 12 mm	16000
160-46	25	0,98	L	M2	25,6	7 x 12 mm	16000
160-47	25	0,98	R	M3	25,6	7 x 12 mm	16000
160-48	25	0,98	L	M3	25,6	7 x 12 mm	16000
160-49	25	0,98	R	M4	25,6	7 x 12 mm	16000
160-50	25	0,98	L	M4	25,6	7 x 12 mm	16000
160-01	30	1,20	R	M4	26,7	8 x 14,5 mm	14500
160-02	30	1,20	L	M4	26,7	8 x 14,5 mm	14500
160-01A	30	1,20	R	M3	26,7	8 x 14,5 mm	14500
160-02A	30	1,20	L	M3	26,7	8 x 14,5 mm	14500

160 - 3 blade

METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
160-03	35	1,40	R	M4	31,1	8 x 14,5 mm	14500
160-04	35	1,40	L	M4	31,1	8 x 14,5 mm	14500
106-03A	35	1,40	R	M3	31,1	8 x 14,5 mm	14500
160-04A	35	1,40	L	M3	31,1	8 x 14,5 mm	14500
160-05	40	1,60	R	M4	35,6	9 x 16 mm	13000
160-06	40	1,60	L	M4	35,6	9 x 16 mm	13000
160-07	45	1,80	R	M4	40,0	9 x 16 mm	12000
160-08	45	1,80	L	M4	40,0	9 x 16 mm	12000
160-09	50	2,00	R	M4	44,5	10 x 18 mm	10000
160-10	50	2,00	L	M4	44,5	10 x 18 mm	10000
160-11	55	2,20	R	M4	49,0	10 x 18 mm	9600
160-12	55	2,20	L	M4	49,0	10 x 18 mm	9600
160-13	60	2,40	R	M4	53,3	11 x 22 mm	8000
160-14	60	2,40	L	M4	53,3	11 x 22 mm	8000
160-15	60	2,40	R	M5	53,3	11 x 22 mm	8000
160-16	60	2,40	L	M5	53,3	11 x 22 mm	8000




161 / C-type



161 - 3 blade

INCH shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
161-05	40	1,60	R	3/16	35,6	9 x 16 mm	13000
161-06	40	1,60	L	3/16	35,6	9 x 16 mm	13000
161-07	45	1,80	R	3/16	40,0	9 x 16 mm	12000
161-08	45	1,80	L	3/16	40,0	9 x 16 mm	12000
161-09	50	2,00	R	3/16	44,5	10 x 18 mm	10000
161-10	50	2,00	L	3/16	44,5	10 x 18 mm	10000



162 / D-type



162 - 3 blade

METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
162-01	20	0,79	R	M2	20,5	6 x 15 mm	16000
162-02	20	0,79	L	M2	20,5	6 x 15 mm	16000
162-03	20	0,79	R	M3	20,5	6 x 15 mm	16000
162-04	20	0,79	L	M3	20,5	6 x 15 mm	16000
162-05	20	0,79	R	M4	20,5	6 x 15 mm	16000
162-06	20	0,79	L	M4	20,5	6 x 15 mm	16000

Brass propellers

Messing sloopsschroeven - Messing Schiffsschrauben - Hélices laiton



162 - 3 blade

METRIC shaft connection


Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
162-41	23,5	0,93	R	M2	22,8	6 x 15 mm	16000
162-42	23,5	0,93	L	M2	22,8	6 x 15 mm	16000
162-43	23,5	0,93	R	M3	22,8	6 x 15 mm	16000
162-44	23,5	0,93	L	M3	22,8	6 x 15 mm	16000
162-07	25	0,98	R	M2	25,6	7 x 16 mm	16000
162-08	25	0,98	L	M2	25,6	7 x 16 mm	16000
162-09	25	0,98	R	M3	25,6	7 x 16 mm	16000
162-10	25	0,98	L	M3	25,6	7 x 16 mm	16000
162-11	25	0,98	R	M4	25,6	7 x 16 mm	16000
162-12	25	0,98	L	M4	25,6	7 x 16 mm	16000
162-13	30	1,20	R	M4	26,7	8 x 20 mm	14500
162-14	30	1,20	L	M4	26,7	8 x 20 mm	14500
162-13A	30	1,20	R	M3	26,7	8 x 20 mm	14500
162-14A	30	1,20	L	M3	26,7	8 x 20 mm	14500
162-15	35	1,40	R	M4	31,1	8 x 20 mm	14500
162-16	35	1,40	L	M4	31,1	8 x 20 mm	14500
162-17	40	1,60	R	M4	35,6	9x 21,5 mm	13000
162-18	40	1,60	L	M4	35,6	9x 21,5 mm	13000
162-19	45	1,80	R	M4	40,0	9x 21,5 mm	12000
162-20	45	1,80	L	M4	40,0	9x 21,5 mm	12000
162-21	50	2,00	R	M4	44,5	10 x 23 mm	10000
162-22	50	2,00	L	M4	44,5	10 x 23 mm	10000
162-23	55	2,20	R	M4	49,0	10 x 23 mm	9600
162-24	55	2,20	L	M4	49,0	10 x 23 mm	9600

163 - 6 blade

METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
163-21	50	2,00	R	M4	44,5	9 x 16 mm	10000
163-22	50	2,00	L	M4	44,5	9 x 16 mm	10000
163-23	55	2,20	R	M4	49,0	9 x 16 mm	9600
163-24	55	2,20	L	M4	49,0	9 x 16 mm	9600
163-25	60	2,40	R	M4	53,3	10 x 18 mm	8000
163-26	60	2,40	L	M4	53,3	10 x 18 mm	8000
163-27	60	2,40	R	M5	53,3	10 x 18 mm	8000
163-28	60	2,40	L	M5	53,3	10 x 18 mm	8000

164 / D-type



164 - 6 blade

METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
164-01	20	0,79	R	M2	20,5	5 x 13 mm	16000
164-02	20	0,79	L	M2	20,5	5 x 13 mm	16000
164-03	20	0,79	R	M3	20,5	5 x 13 mm	16000
164-04	20	0,79	L	M3	20,5	5 x 13 mm	16000
164-05	25	0,98	R	M2	25,6	6 x 15 mm	16000
164-06	25	0,98	L	M2	25,6	6 x 15 mm	16000
164-07	25	0,98	R	M3	25,6	6 x 15 mm	16000
164-08	25	0,98	L	M3	25,6	6 x 15 mm	16000
164-09	25	0,98	R	M4	25,6	6 x 15 mm	16000
164-10	25	0,98	L	M4	25,6	6 x 15 mm	16000
164-11	30	1,20	R	M3	26,7	7 x 16 mm	14500
164-12	30	1,20	L	M3	26,7	7 x 16 mm	14500
164-13	30	1,20	R	M4	26,7	7 x 16 mm	14500
164-14	30	1,20	L	M4	26,7	7 x 16 mm	14500
164-15	35	1,40	R	M4	31,1	7 x 16 mm	14500
164-16	35	1,40	L	M4	31,1	7 x 16 mm	14500
164-17	40	1,60	R	M4	35,6	8 x 20 mm	13000
164-18	40	1,60	L	M4	35,6	8 x 20 mm	13000
164-19	45	1,80	R	M4	40,0	8 x 20 mm	12000
164-20	45	1,80	L	M4	40,0	8 x 20 mm	12000
164-21	50	2,00	R	M4	44,5	9x 21,5 mm	10000
164-22	50	2,00	L	M4	44,5	9x 21,5 mm	10000
164-23	55	2,20	R	M4	49,0	9x 21,5 mm	9600
164-24	55	2,20	L	M4	49,0	9x 21,5 mm	9600
164-25	60	2,40	R	M4	53,3	10 x 23 mm	8000
164-26	60	2,40	L	M4	53,3	10 x 23 mm	8000
164-27	60	2,40	R	M5	53,3	10 x 23 mm	8000
164-28	60	2,40	L	M5	53,3	10 x 23 mm	8000

163 / D-type




163 - 6 blade

METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
163-01	20	0,79	R	M2	20,5	5 x 9 mm	16000
163-02	20	0,79	L	M2	20,5	5 x 9 mm	16000
163-03	20	0,79	R	M3	20,5	5 x 9 mm	16000
163-04	20	0,79	L	M3	20,5	5 x 9 mm	16000
163-05	25	0,98	R	M2	25,6	6 x 10 mm	16000
163-06	25	0,98	L	M2	25,6	6 x 10 mm	16000
163-07	25	0,98	R	M3	25,6	6 x 10 mm	16000
163-08	25	0,98	L	M3	25,6	6 x 10 mm	16000
163-09	25	0,98	R	M4	25,6	6 x 10 mm	16000
163-10	25	0,98	L	M4	25,6	6 x 10 mm	16000
163-11	30	1,20	R	M3	26,7	7 x 12 mm	14500
163-12	30	1,20	L	M3	26,7	7 x 12 mm	14500
163-13	30	1,20	R	M4	26,7	7 x 12 mm	14500
163-14	30	1,20	L	M4	26,7	7 x 12 mm	14500
163-15	35	1,40	R	M4	31,1	7 x 12 mm	14500
163-16	35	1,40	L	M4	31,1	7 x 12 mm	14500
163-17	40	1,60	R	M4	35,6	8 x 14,5 mm	13000
163-18	40	1,60	L	M4	35,6	8 x 14,5 mm	13000
163-19	45	1,80	R	M4	40,0	8 x 14,5 mm	12000
163-20	45	1,80	L	M4	40,0	8 x 14,5 mm	12000

Brass propellers

Messing sloopsschroeven - Messing Schiffsschrauben - Hélices laiton




168 / C-type



168 - 5 blade

METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
168-01	20	0,79	R	M2	20,5	6 x 15 mm	16000
168-02	20	0,79	L	M2	20,5	6 x 15 mm	16000
168-03	20	0,79	R	M3	20,5	6 x 15 mm	16000
168-04	20	0,79	L	M3	20,5	6 x 15 mm	16000
168-05	20	0,79	R	M4	20,5	6 x 15 mm	16000
168-06	20	0,79	L	M4	20,5	6 x 15 mm	16000
168-07	25	0,98	R	M3	25,6	7 x 16 mm	16000
168-08	25	0,98	L	M3	25,6	7 x 16 mm	16000
168-09	25	0,98	R	M4	25,6	7 x 16 mm	16000
168-10	25	0,98	L	M4	25,6	7 x 16 mm	16000
168-11	30	1,20	R	M4	26,7	8 x 20 mm	14500
168-12	30	1,20	L	M4	26,7	8 x 20 mm	14500
168-11A	30	1,20	R	M3	26,7	8 x 20 mm	14500
168-12A	30	1,20	L	M3	26,7	8 x 20 mm	14500
168-13	35	1,40	R	M4	31,1	8 x 20 mm	14500
168-14	35	1,40	L	M4	31,1	8 x 20 mm	14500
168-13A	35	1,40	R	M3	32,1	8 x 20 mm	14500
168-14A	35	1,40	L	M3	32,1	8 x 20 mm	14500
168-15	40	1,60	R	M4	35,6	9 x 21,5 mm	13000
168-16	40	1,60	L	M4	35,6	9 x 21,5 mm	13000
168-17	45	1,80	R	M4	40,0	9 x 21,5 mm	12000
168-18	45	1,80	L	M4	40,0	9 x 21,5 mm	12000
168-19	50	2,00	R	M4	44,5	10 x 23 mm	10000
168-20	50	2,00	L	M4	44,5	10 x 23 mm	10000
168-21	55	2,20	R	M4	49,0	10 x 23 mm	9600
168-22	55	2,20	L	M4	49,0	10 x 23 mm	9600



170 / C-type



170 - 4 blade

METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
170-41	20	0,79	R	M2	20,5	5 x 9 mm	16000
170-42	20	0,79	L	M2	20,5	5 x 9 mm	16000
170-43	20	0,79	R	M3	20,5	5 x 9 mm	16000
170-44	20	0,79	L	M3	20,5	5 x 9 mm	16000
170-45	25	0,98	R	M2	25,6	7 x 12 mm	16000
170-46	25	0,98	L	M2	25,6	7 x 12 mm	16000
170-01	25	0,98	R	M3	25,6	7 x 12 mm	16000
170-02	25	0,98	L	M3	25,6	7 x 12 mm	16000

170 - 4 blade

METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
170-01A	25	0,98	R	M4	25,6	7 x 12 mm	16000
170-02A	25	0,98	L	M4	25,6	7 x 12 mm	16000
170-47	30	1,20	R	M3	26,7	8 x 14,5 mm	14500
170-48	30	1,20	L	M3	26,7	8 x 14,5 mm	14500
170-03	30	1,20	R	M4	26,7	8 x 14,5 mm	14500
170-04	30	1,20	L	M4	26,7	8 x 14,5 mm	14500
170-49	35	1,40	R	M3	31,1	8 x 14,5 mm	14500
170-50	35	1,40	L	M3	31,1	8 x 14,5 mm	14500
170-03A	35	1,40	R	M4	31,1	8 x 14,5 mm	14500
170-04A	35	1,40	L	M4	31,1	8 x 14,5 mm	14500
170-05	40	1,60	R	M4	35,6	9 x 16 mm	13000
170-06	40	1,60	L	M4	35,6	9 x 16 mm	13000
170-07	45	1,80	R	M4	40,0	9 x 16 mm	12000
170-08	45	1,80	L	M4	40,0	9 x 16 mm	12000
170-09	50	2,00	R	M4	44,5	10 x 18 mm	10000
170-10	50	2,00	L	M4	44,5	10 x 18 mm	10000
170-11	55	2,20	R	M4	49,0	10 x 18 mm	9600
170-12	55	2,20	L	M4	49,0	10 x 18 mm	9600
170-13	60	2,40	R	M4	53,3	11 x 22 mm	8000
170-14	60	2,40	L	M4	53,3	11 x 22 mm	8000
170-13A	60	2,40	R	M5	53,3	11 x 22 mm	8000
170-14A	60	2,40	L	M5	53,3	11 x 22 mm	8000
170-15	65	2,60	R	M4	57,7	11 x 22 mm	6600
170-16	65	2,60	L	M4	57,7	11 x 22 mm	6600
170-15A	65	2,60	R	M5	57,7	11 x 22 mm	6600
170-16A	65	2,60	L	M5	57,7	11 x 22 mm	6600
170-17	70	2,80	R	M4	62,2	12 x 24 mm	6200
170-18	70	2,80	L	M4	62,2	12 x 24 mm	6200
170-17A	70	2,80	R	M5	62,2	12 x 24 mm	6200
170-18A	70	2,80	L	M5	62,2	12 x 24 mm	6200



171 / C-type



171 - 4 blade

INCH shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
171-05	40	1,60	R	3/16	35,6	9 x 16 mm	13000
171-06	40	1,60	L	3/16	35,6	9 x 16 mm	13000
171-07	45	1,80	R	3/16	40,0	9 x 16 mm	12000
171-08	45	1,80	L	3/16	40,0	9 x 16 mm	12000
171-09	50	2,00	R	3/16	44,5	10 x 18 mm	10000
171-10	50	2,00	L	3/16	44,5	10 x 18 mm	10000
171-11	55	2,20	R	3/16	49,0	10 x 18 mm	9600
171-12	55	2,20	L	3/16	49,0	10 x 18 mm	9600
171-13	60	2,40	R	3/16	53,3	11 x 22 mm	8000
171-14	60	2,40	L	3/16	53,3	11 x 22 mm	8000
171-15	65	2,60	R	3/16	57,7	11 x 22 mm	6600
171-16	65	2,60	L	3/16	57,7	11 x 22 mm	6600
171-17	70	2,80	R	3/16	62,2	12 x 24 mm	6200
171-18	70	2,80	L	3/16	62,2	12 x 24 mm	6200

Brass propellers

Messing sloopsschroeven - Messing Schiffsschrauben - Hélices laiton




172 / B-type



172 - 6 blade

METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
172-05	40	1,60	R	M4	41,0	9 x 16 mm	13000
172-06	40	1,60	L	M4	41,0	9 x 16 mm	13000
172-07	45	1,80	R	M4	46,1	9 x 16 mm	12000
172-08	45	1,80	L	M4	46,1	9 x 16 mm	12000
172-09	50	2,00	R	M4	51,2	10 x 18 mm	10000
172-10	50	2,00	L	M4	51,2	10 x 18 mm	10000
172-11	55	2,20	R	M4	56,4	10 x 18 mm	9600
172-12	55	2,20	L	M4	56,4	10 x 18 mm	9600
172-13	60	2,40	R	M4	61,5	11 x 22 mm	8000
172-14	60	2,40	L	M4	61,5	11 x 22 mm	8000
172-13A	60	2,40	R	M5	61,5	11 x 22 mm	8000
172-14A	60	2,40	L	M5	61,5	11 x 22 mm	8000
172-15	65	2,60	R	M4	66,6	11 x 22 mm	6600
172-16	65	2,60	L	M4	66,6	11 x 22 mm	6600
172-15A	65	2,60	R	M5	66,6	11 x 22 mm	6600
172-16A	65	2,60	L	M5	66,6	11 x 22 mm	6600
172-17	70	2,80	R	M4	71,7	12 x 24 mm	6200
172-18	70	2,80	L	M4	71,7	12 x 24 mm	6200
172-17A	70	2,80	R	M5	71,7	12 x 24 mm	6200
172-18A	70	2,80	L	M5	71,7	12 x 24 mm	6200



174 / D-type



174 - 4 blade

METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
174-41	20	0,79	R	M2	20,5	6 x 10 mm	16000
174-42	20	0,79	L	M2	20,5	6 x 10 mm	16000
174-43	20	0,79	R	M3	20,5	6 x 10 mm	16000
174-44	20	0,79	L	M3	20,5	6 x 10 mm	16000
174-45	25	0,98	R	M2	25,6	7 x 12 mm	16000
174-46	25	0,98	L	M2	25,6	7 x 12 mm	16000
174-47	25	0,98	R	M3	25,6	7 x 12 mm	16000
174-48	25	0,98	L	M3	25,6	7 x 12 mm	16000
174-49	25	0,98	R	M4	25,6	7 x 12 mm	16000
174-50	25	0,98	L	M4	25,6	7 x 12 mm	16000
174-01	30	1,20	R	M4	26,7	8 x 14,5 mm	14500
174-02	30	1,20	L	M4	26,7	8 x 14,5 mm	14500
174-01A	30	1,20	R	M3	26,7	8 x 14,5 mm	14500
174-02A	30	1,20	L	M3	26,7	8 x 14,5 mm	14500
174-03	35	1,40	R	M4	31,1	8 x 14,5 mm	14500
174-04	35	1,40	L	M4	31,1	8 x 14,5 mm	14500
174-03A	35	1,40	R	M3	31,1	8 x 14,5 mm	14500
174-04A	35	1,40	L	M3	31,1	8 x 14,5 mm	14500
174-05	40	1,60	R	M4	35,6	9 x 16 mm	13000
174-06	40	1,60	L	M4	35,6	9 x 16 mm	13000
174-07	45	1,80	R	M4	40,0	9 x 16 mm	12000
174-08	45	1,80	L	M4	40,0	9 x 16 mm	12000
174-09	50	2,00	R	M4	44,5	10 x 18 mm	10000
174-10	50	2,00	L	M4	44,5	10 x 18 mm	10000
174-11	55	2,20	R	M4	49,0	10 x 18 mm	9600
174-12	55	2,20	L	M4	49,0	10 x 18 mm	9600
174-13	60	2,40	R	M4	53,3	11 x 22 mm	8000
174-14	60	2,40	L	M4	53,3	11 x 22 mm	8000
174-13A	60	2,40	R	M5	53,3	11 x 22 mm	8000
174-14A	60	2,40	L	M5	53,3	11 x 22 mm	8000



173 / B-type




173 - 6 blade

INCH shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
173-05	40	1,60	R	3/16	41,0	9 x 16 mm	13000
173-06	40	1,60	L	3/16	41,0	9 x 16 mm	13000
173-07	45	1,80	R	3/16	46,1	9 x 16 mm	12000
173-08	45	1,80	L	3/16	46,1	9 x 16 mm	12000
173-09	50	2,00	R	3/16	51,2	10 x 18 mm	10000
173-10	50	2,00	L	3/16	51,2	10 x 18 mm	10000
173-11	55	2,20	R	3/16	56,4	10 x 18 mm	9600
173-12	55	2,20	L	3/16	56,4	10 x 18 mm	9600

Brass propellers

Messing sloopsschroeven - Messing Schiffsschrauben - Hélices laiton



175 / D-type



175 - 4 blade


INCH shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
175-01	30	1,20	R	3/16	26,7	8 x 14,5 mm	14500
175-02	30	1,20	L	3/16	26,7	8 x 14,5 mm	14500
175-03	35	1,40	R	3/16	31,1	8 x 14,5 mm	14500
175-04	35	1,40	L	3/16	31,1	8 x 14,5 mm	14500
175-05	40	1,60	R	3/16	35,6	9 x 16 mm	13000
175-06	40	1,60	L	3/16	35,6	9 x 16 mm	13000
175-07	45	1,80	R	3/16	40,0	9 x 16 mm	12000
175-08	45	1,80	L	3/16	40,0	9 x 16 mm	12000
175-09	50	2,00	R	3/16	44,5	10 x 18 mm	10000
175-10	50	2,00	L	3/16	44,5	10 x 18 mm	10000
175-11	55	2,20	R	3/16	49,0	10 x 18 mm	9600
175-12	55	2,20	L	3/16	49,0	10 x 18 mm	9600
175-13	60	2,40	R	3/16	53,3	11 x 22 mm	8000
175-14	60	2,40	L	3/16	53,3	11 x 22 mm	8000

176 - 3 blade

INCH shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
176-19	60	2,40	R	3/16	61,5	11 x 22 mm	8000
176-20	60	2,40	L	3/16	61,5	11 x 22 mm	8000
176-21	65	2,60	R	3/16	66,6	11 x 22 mm	6600
176-22	65	2,60	L	3/16	66,6	11 x 22 mm	6600
176-23	70	2,80	R	3/16	71,7	12 x 24 mm	6200
176-24	70	2,80	L	3/16	71,7	12 x 24 mm	6200
176-25	75	3,00	R	3/16	76,9	12 x 24 mm	4200
176-26	75	3,00	L	3/16	76,9	12 x 24 mm	4200
176-27	80	3,20	R	3/16	82,0	13 x 26 mm	3500
176-28	80	3,20	L	3/16	82,0	13 x 26 mm	3500
176-29	90	3,60	R	3/16	92,2	14 x 28 mm	3100
176-30	90	3,60	L	3/16	92,2	14 x 28 mm	3100



177 / A-type



177 - 4 blade

INCH shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
177-39	20	0,79	R	1/8	20,5	6 x 10 mm	16000
177-40	20	0,79	L	1/8	20,5	6 x 10 mm	16000
177-41	25	0,98	R	1/8	25,6	7 x 12 mm	16000
177-42	25	0,98	L	1/8	25,6	7 x 12 mm	16000
177-43	30	1,20	R	1/8	30,7	8 x 14,5 mm	14500
177-44	30	1,20	L	1/8	30,7	8 x 14,5 mm	14500
177-01	30	1,20	R	3/16	30,7	8 x 14,5 mm	14500
177-02	30	1,20	L	3/16	30,7	8 x 14,5 mm	14500
177-45	35	1,40	R	1/8	35,9	8 x 14,5 mm	14500
177-46	35	1,40	L	1/8	35,9	8 x 14,5 mm	14500
177-03	35	1,40	R	3/16	35,9	8 x 14,5 mm	14500
177-04	35	1,40	L	3/16	35,9	8 x 14,5 mm	14500
177-05	40	1,60	R	3/16	41,0	9 x 16 mm	13000
177-06	40	1,60	L	3/16	41,0	9 x 16 mm	13000
177-07	45	1,80	R	3/16	46,1	9 x 16 mm	12000
177-08	45	1,80	L	3/16	46,1	9 x 16 mm	12000
177-11	50	2,00	R	3/16	51,2	10 x 18 mm	10000
177-12	50	2,00	L	3/16	51,2	10 x 18 mm	10000
177-15	55	2,20	R	3/16	56,4	10 x 18 mm	9600
177-16	55	2,20	L	3/16	56,4	10 x 18 mm	9600
177-19	60	2,40	R	3/16	61,5	11 x 22 mm	8000
177-20	60	2,40	L	3/16	61,5	11 x 22 mm	8000
177-21	65	2,60	R	3/16	66,6	11 x 22 mm	6600
177-22	65	2,60	L	3/16	66,6	11 x 22 mm	6600
177-23	70	2,80	R	3/16	71,7	12 x 24 mm	6200
177-24	70	2,80	L	3/16	71,7	12 x 24 mm	6200
177-25	75	3,00	R	3/16	76,9	12 x 24 mm	4200
177-26	75	3,00	L	3/16	76,9	12 x 24 mm	4200
177-27	80	3,20	R	3/16	82,0	13 x 26 mm	3500
177-28	80	3,20	L	3/16	82,0	13 x 26 mm	3500
177-29	90	3,60	R	3/16	92,2	14 x 28 mm	3100
177-30	90	3,60	L	3/16	92,2	14 x 28 mm	3100

176 - 3 blade

INCH shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
176-39	20	0,79	R	1/8	20,5	6 x 10 mm	16000
176-40	20	0,79	L	1/8	20,5	6 x 10 mm	16000
176-41	25	0,98	R	1/8	25,6	7 x 12 mm	16000
176-42	25	0,98	L	1/8	25,6	7 x 12 mm	16000
176-43	30	1,20	R	1/8	30,7	8 x 14,5 mm	14500
176-44	30	1,20	L	1/8	30,7	8 x 14,5 mm	14500
176-01	30	1,20	R	3/16	30,7	8 x 14,5 mm	14500
176-02	30	1,20	L	3/16	30,7	8 x 14,5 mm	14500
176-45	35	1,40	R	1/8	35,9	8 x 14,5 mm	14500
176-46	35	1,40	L	1/8	35,9	8 x 14,5 mm	14500
176-03	35	1,40	R	3/16	35,9	8 x 14,5 mm	14500
176-04	35	1,40	L	3/16	35,9	8 x 14,5 mm	14500
176-05	40	1,60	R	3/16	41,0	9 x 16 mm	13000
176-06	40	1,60	L	3/16	41,0	9 x 16 mm	13000
176-07	45	1,80	R	3/16	46,1	9 x 16 mm	12000
176-08	45	1,80	L	3/16	46,1	9 x 16 mm	12000
176-11	50	2,00	R	3/16	51,2	10 x 18 mm	10000
176-12	50	2,00	L	3/16	51,2	10 x 18 mm	10000
176-15	55	2,20	R	3/16	56,4	10 x 18 mm	9600
176-16	55	2,20	L	3/16	56,4	10 x 18 mm	9600

Brass propellers

Messing sloopsschroeven - Messing Schiffsschrauben - Hélices laiton



178 / A-type



178 - 5 blade

INCH shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
178-01	30	1,20	R	3/16	30,7	8 x 14,5 mm	14500
178-02	30	1,20	L	3/16	30,7	8 x 14,5 mm	14500
178-03	35	1,40	R	3/16	35,9	8 x 14,5 mm	14500
178-04	35	1,40	L	3/16	35,9	8 x 14,5 mm	14500
178-05	40	1,60	R	3/16	41,0	9 x 16 mm	13000
178-06	40	1,60	L	3/16	41,0	9 x 16 mm	13000
178-07	45	1,80	R	3/16	46,1	9 x 16 mm	12000
178-08	45	1,80	L	3/16	46,1	9 x 16 mm	12000
178-09	50	2,00	R	3/16	51,2	10 x 18 mm	10000
178-10	50	2,00	L	3/16	51,2	10 x 18 mm	10000
178-11	55	2,20	R	3/16	56,4	10 x 18 mm	9600
178-12	55	2,20	L	3/16	56,4	10 x 18 mm	9600
178-13	60	2,40	R	3/16	61,5	11 x 22 mm	8000
178-14	60	2,40	L	3/16	61,5	11 x 22 mm	8000
178-15	65	2,60	R	3/16	66,6	11 x 22 mm	6600
178-16	65	2,60	L	3/16	66,6	11 x 22 mm	6600
178-17	70	2,80	R	3/16	71,7	12 x 24 mm	6200
178-18	70	2,80	L	3/16	71,7	12 x 24 mm	6200



180 / B-type



180 - 7 blade

INCH shaft connection side screw M3 x 4mm included

Code	D mm	D inch	R/L	shaft hole	Hub Ø x Length	RPM max.
180-13	53	2,08	R	Ø 3/16	18 x 25 mm	9600
180-14	53	2,08	L	Ø 3/16	18 x 25 mm	9600
180-15	58	2,28	R	Ø 3/16	18 x 25 mm	8000
180-16	58	2,28	L	Ø 3/16	18 x 25 mm	8000
180-17	63	2,48	R	Ø 3/16	19 x 26 mm	6600
180-18	63	2,48	L	Ø 3/16	19 x 26 mm	6600
180-19	68	2,68	R	Ø 3/16	19 x 26 mm	6200
180-20	68	2,68	L	Ø 3/16	19 x 26 mm	6200
180-23	73	2,87	R	Ø 3/16	20 x 27 mm	4200
180-24	73	2,87	L	Ø 3/16	20 x 27 mm	4200
180-27	78	3,07	R	Ø 3/16	20 x 27 mm	3500
180-28	78	3,07	L	Ø 3/16	20 x 27 mm	3500



179 / B-type



179 - 7 blade

METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	Hub Ø x Length	RPM max.
179-13	53	2,08	R	M5	18 x 25 mm	9600
179-14	53	2,08	L	M5	18 x 25 mm	9600
179-15	58	2,28	R	M5	18 x 25 mm	8000
179-16	58	2,28	L	M5	18 x 25 mm	8000
179-17	63	2,48	R	M5	19 x 26 mm	6600
179-18	63	2,48	L	M5	19 x 26 mm	6600
179-19	68	2,68	R	M5	19 x 26 mm	6200
179-20	68	2,68	L	M5	19 x 26 mm	6200
179-23	73	2,87	R	M5	20 x 27 mm	4200
179-24	73	2,87	L	M5	20 x 27 mm	4200
179-27	78	3,07	R	M5	20 x 27 mm	3500
179-28	78	3,07	L	M5	20 x 27 mm	3500



181 / A-type



181 - 5 blade

METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	Hub Ø x Length	RPM max.
181-13	55	2,2	R	M4	15x22 mm	9600
181-14	55	2,2	L	M4	15x22 mm	9600
181-13A	55	2,2	R	M5	15x22 mm	9600
181-14A	55	2,2	L	M5	15x22 mm	9600
181-15	60	2,4	R	M4	16x23 mm	8000
181-16	60	2,4	L	M4	16x23 mm	8000
181-15A	60	2,4	R	M5	16x23 mm	8000
181-16A	60	2,4	L	M5	16x23 mm	8000
181-17	65	2,6	R	M5	17x24 mm	6600
181-18	65	2,6	L	M5	17x24 mm	6600
181-19	70	2,8	R	M5	17x24 mm	6200
181-20	70	2,8	L	M5	17x24 mm	6200
181-21	75	3,0	R	M5	18x25 mm	4200
181-22	75	3,0	L	M5	18x25 mm	4200
181-23	80	3,2	R	M5	19x26 mm	3500
181-24	80	3,2	L	M5	19x26 mm	3500
181-25	85	3,4	R	M5	20x27 mm	3100
181-26	85	3,4	L	M5	20x27 mm	3100
181-27	95	3,8	R	M5	20x27 mm	2800
181-28	95	3,8	L	M5	20x27 mm	2800

Brass propellers

Messing sloopsschroeven - Messing Schiffsschrauben - Hélices laiton



183 / C-type



183 - 5 blade

METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
183-13	55	2,2	R	M4		15x22 mm	9600
183-14	55	2,2	L	M4		15x22 mm	9600
183-13A	55	2,2	R	M5		15x22 mm	9600
183-14A	55	2,2	L	M5		15x22 mm	9600
183-15	60	2,4	R	M4		16x23 mm	8000
183-16	60	2,4	L	M4		16x23 mm	8000
183-15A	60	2,4	R	M5		16x23 mm	8000
183-16A	60	2,4	L	M5		16x23 mm	8000
183-17	65	2,6	R	M5		17x24 mm	6600
183-18	65	2,6	L	M5		17x24 mm	6600
183-19	70	2,8	R	M5		18x25 mm	6200
183-20	70	2,8	L	M5		18x25 mm	6200
183-21	75	3,0	R	M5		19x26 mm	4200
183-22	75	3,0	L	M5		19x26 mm	4200



186 / B-type



186 - 7 blade

INCH shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
186-05	40	1,60	R	3/16	41,0	9 x 16 mm	13000
186-06	40	1,60	L	3/16	41,0	9 x 16 mm	13000
186-07	45	1,80	R	3/16	46,1	9 x 16 mm	12000
186-08	45	1,80	L	3/16	46,1	9 x 16 mm	12000
186-09	50	2,00	R	3/16	51,2	10 x 18 mm	10000
186-10	50	2,00	L	3/16	51,2	10 x 18 mm	10000
186-11	55	2,20	R	3/16	56,4	10 x 18 mm	9600
186-12	55	2,20	L	3/16	56,4	10 x 18 mm	9600



185 / B-type



185 - 7 blade

METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
185-05	40	1,60	R	M4	41,0	9 x 16 mm	13000
185-06	40	1,60	L	M4	41,0	9 x 16 mm	13000
185-07	45	1,80	R	M4	46,1	9 x 16 mm	12000
185-08	45	1,80	L	M4	46,1	9 x 16 mm	12000
185-09	50	2,00	R	M4	51,2	10 x 18 mm	10000
185-10	50	2,00	L	M4	51,2	10 x 18 mm	10000
185-11	55	2,20	R	M4	56,4	10 x 18 mm	9600
185-12	55	2,20	L	M4	56,4	10 x 18 mm	9600
185-13	60	2,40	R	M4	61,5	11 x 22 mm	8000
185-14	60	2,40	L	M4	61,5	11 x 22 mm	8000
185-13A	60	2,40	R	M5	61,5	11 x 22 mm	8000
185-14A	60	2,40	L	M5	61,5	11 x 22 mm	8000
185-15	65	2,60	R	M4	66,6	11 x 22 mm	6600
185-16	65	2,60	L	M4	66,6	11 x 22 mm	6600
185-15A	65	2,60	R	M5	66,6	11 x 22 mm	6600
185-16A	65	2,60	L	M5	66,6	11 x 22 mm	6600
185-17	70	2,80	R	M4	71,7	12 x 24 mm	6200
185-18	70	2,80	L	M4	71,7	12 x 24 mm	6200
185-17A	70	2,80	R	M5	71,7	12 x 24 mm	6200
185-18A	70	2,80	L	M5	71,7	12 x 24 mm	6200

RC Transmitter Neck Straps

RC zender banden - RC Sender tragegurts - Sangle de radio-commande



109 - 01 Single hook RC Transmitter Neck Strap



Overall length: 124 cm max.
Effective length: 57 cm max.
Number of hooks: 1

109 - 02 Double hook RC Transmitter Neck Strap



Overall length: 124 cm max.
Effective length: 57 cm max.
Number of hooks: 2

124 cm max.



Brass propellers Raboesch special series



140 - 06



184 - 13



www.engel-modellbau.de

140 - 06

6 blade propeller
for RC Submarine Neptune SB-1

METRIC shaft connection
side screw M2,5 x 3mm included

Code	D mm	D inch	R/L	shaft hole	pitch mm	Hub Ø x Length	RPM max.
140-06	40	1.60	L	Ø 4 mm	41,0	9 x 14mm	13000

184 - 13


6 blade propeller
for Type 212A Class RC Submarine

METRIC shaft connection

Code	D mm	D inch	R/L	shaft thread	pitch mm	Hub Ø x Length	RPM max.
184-13	60	2,40	R	M4	71,7	12 x 12mm	8000


Rubber Bumper profile

Rubber stootrand profiel - Gummi Stoßfänger Profile - Liston de protection en caoutchouc




104-30 > 34 Rubber bump profile round absorbers

Code	A mm	B mm	° shore	length	content
104-30	Ø 2	0,5	60°	200 cm	1
104-31	Ø 4	1	60°	200 cm	1
104-32	Ø 6	1	60°	200 cm	1
104-33	Ø 8	2	60°	200 cm	1
104-34	Ø 10	2	60°	200 cm	1




104-50 > 54 Rubber bump profile square absorbers

Code	A mm	B mm	C mm	° shore	length	content
104-50	2	2	0,75	60°	200 cm	1
104-51	4	3	1,5	60°	200 cm	1
104-52	6	4	3	60°	200 cm	1
104-53	8	4,8	4	60°	200 cm	1
104-54	10	7	6	60°	200 cm	1




104-60 > 64 Rubber bump profile half round absorbers

Code	A mm	B mm	° shore	length	content
104-60	2	1,1	60°	200 cm	1
104-61	4	2,1	60°	200 cm	1
104-62	6	3,1	60°	200 cm	1
104-63	8	4,2	60°	200 cm	1
104-64	10	5,2	60°	200 cm	1



104-72 > 74 Rubber bump profile rounded square absorbers

Code	A mm	B mm	C mm	length	content
104-72	6	5	2	200 cm	1
104-73	8	7	3	200 cm	1
104-74	10	9	4	200 cm	1




Rubber Bumper sheet

Rubber stootrand plaat - Gummi Stoßfänger Platte - Liston de protection en caoutchouc


104-21 > 24

Rubber bump sheet


Code	L x W	° shore	A mm	B mm	C mm	D mm	content
104-21	300 x 75 mm	60°	1,7	1,5	3	1,7	1
104-23	300 x 75 mm	70°	3	3,5	3,1	1,6	1
104-24	300 x 100 mm	45°	3,5	4,2	8,5	4,8	1



104-21





104-23



104-24

104-26 Rubber bump sheet

Code	L x W	A mm	B mm	C mm	D mm	content
104-26	600 x 120 mm	12,00	6,00	6,00	3,00	1



Electric Motors

Electrische motoren - Elektromotoren - Moteurs Électriques




109 - 13 Blue RM130 Brushed Motor 12 Volt

RM-100 Series



Nom. Voltage: 12V
Voltage Range: 6-12V
Shaft: Ø 2 mm
Weight: 22 gr

	No load	Max. Efficiency	Max. Output
Current:	10 mA	0,6 A	0,7 A
Speed:	15.500 Rpm	9250 Rpm	4300 Rpm




109 - 40 Blue RM400 Brushed Motor 6 Volt

RM-400 Series



Nom. Voltage: 6V
Voltage Range: 3-6V
Shaft: Ø 2,3 mm
Weight: 72 gr

	No load	Max. Efficiency	Max. Output
Current:	0,8 A	1,6 A	3,4 A
Speed:	17.000 Rpm	7300 Rpm	4200 Rpm




109 - 41 Blue RM410 Brushed Motor 7,2 Volt

RM-400 Series



Nom. Voltage: 7,2V
Voltage Range: 6-9V
Shaft: Ø 2,3 mm
Weight: 72 gr

	No load	Max. Efficiency	Max. Output
Current:	0,7 A	1,3 A	3,2 A
Speed:	17.000 Rpm	7500 Rpm	4300 Rpm




109 - 43 Blue RM430 Brushed Motor 12 Volt

RM-400 Series



Nom. Voltage: 12V
Voltage Range: 6-16V
Shaft: Ø 2,3 mm
Weight: 72 gr

	No load	Max. Efficiency	Max. Output
Current:	0,56 A	1,3 A	2,9 A
Speed:	16.500 Rpm	8000 Rpm	4500 Rpm



RABOESCH®

Electric Motors

Electrische motoren - Elektromotoren - Moteurs Électriques



hobby products


109 - 51 Blue RM 510 TRQ Brushed Motor 7,2 Volt

RM-500 Series



Nom. Voltage: 7,2V
Voltage Range: 6-9V
Shaft: \varnothing 3,2 mm
Weight: 174 gr

	No load	Max. Efficiency	Max. Output
Current:	0,7 A	1,6 A	2,2 A
Speed:	7.600 Rpm	7.000 Rpm	5.800 Rpm




109 - 53 Blue RM 530 TRQ Brushed Motor 7,2 Volt

RM-500 Series



Nom. Voltage: 7,2V
Voltage Range: 6-9V
Shaft: \varnothing 3,2 mm
Weight: 174 gr

	No load	Max. Efficiency	Max. Output
Current:	1,2 A	1,9 A	2,9 A
Speed:	12.000 Rpm	10.500 Rpm	8.200 Rpm




109 - 72 Blue RM 720 BB Turbo Brushed Motor 9,6 Volt

RM-700 Series



Nom. Voltage: 9,6V
Voltage Range: 3-9,6V
Shaft: \varnothing 5 mm
Weight: 352 gr

	No load	Max. Efficiency
Current:	2,0 A	6,3 A
Speed:	15.000 Rpm	6.700 Rpm




109 - 73 Blue RM730TRQ Brushed Motor 12 Volt

RM-700 Series



Nom. Voltage: 12V
Voltage Range: 6-12V
Shaft: \varnothing 5 mm
Weight: 352 gr

	No load	Max. Efficiency
Current:	0,40 A	2,3 A
Speed:	4500 Rpm	3820 Rpm



RABOESCH®


Bow Thrusters

Boegschroeven - Querstrahlruder - Propulseurs d'étrave



Code	A	B	C	D	d	E	F	Max flow at 7,2V
108-01	Ø 22 mm	66 mm	11 mm	Ø 16 mm	Ø 14 mm	31 mm	Ø 40 mm	L/P min at 7,2V
108-02	Ø 22 mm	66 mm	11 mm	Ø 19 mm	Ø 16 mm	31 mm	Ø 40 mm	L/P min at 7,2V
108-03	Ø 22 mm	66 mm	11 mm	Ø 22 mm	Ø 19 mm	31 mm	Ø 40 mm	L/P min at 7,2V
108-04	Ø 28 mm	72 mm	14 mm	Ø 25 mm	Ø 22 mm	34 mm	Ø 40 mm	L/P min at 7,2V
108-05	Ø 28 mm	72 mm	14 mm	Ø 28 mm	Ø 25 mm	34 mm	Ø 40 mm	L/P min at 7,2V

These very powerful bow thrusters are supplied fully mounted with a Blue RM-410 7.2-Volt electrical motor, 11 Amp. max. The propulsion is provided by a flat impeller (paddle) which pressurizes the water through jet nozzles whereby the entire assembly functions as a pump. This design is very robust and very stable and requires very little maintenance. The pump housing and the extension tubes are made of ABS (acrylonitrile butadiene styrene). The motor is sealed with a G-ring and an O-ring which prevents the entry of water whereby the bow thruster can be installed vertically as well as horizontally. The motor with the pump housing cover can be removed easily. The cover has an O-ring that ensures water-tight sealing of the entire assembly. For further technical information: See the dimensional drawing and the technical details of the motor. Blue RM-410 electrical motor. Max. RPM 17.000 – voltage without load: 0.5 Amps Highest performance: 78% - Motor shaft: 2.3 x 12 mm. For spare parts see page 22.



108-01



108-04



108-02



108-05



108-03



Optional motors
6V code 109-40
12V code 109-43
see page 15

For spare parts see page 25.


Bow Thrusters

Boegschroeven - Querstrahlruder - Propulseurs d'étrave

108-20

108-20

The world's smallest bow thruster.
 Blue RM-130 3-12 volt, 6 Amp max. (See page 16: art. 109-13)
 Max. flow: 5,5 L/P min at 12 Volt
 Material: ABS.
 A G-ring ensures water tightness.
 Jet Nozzle diameter \varnothing 10 x 12mm.
 Smallest installation breadth: 21mm.
 Total length: 90mm.
 Total height: 46 mm.
 Weight 30 gr incl. motor.




Jet Nozzle Extension Set

Straalbuis verlengset - Düsenverlängerung Satz - Kit d'extension de tube à jet

108-36 > 45 Jet nozzle extension optional set

Code	For bow thruster	Diameter outside	Diameter inside	Length	Socket	Content
108-39	108-20	\varnothing 12 mm	\varnothing 10 mm	120 mm		2
108-40	108-01	\varnothing 16 mm	\varnothing 14 mm	200 mm	\varnothing 18 x 16 x 40 mm	2
108-41	108-02	\varnothing 16 mm	\varnothing 19 mm	200 mm	\varnothing 19 x 21 x 40 mm	2
108-42	108-03	\varnothing 22 mm	\varnothing 19 mm	200 mm		2
108-43	108-04	\varnothing 25 mm	\varnothing 22 mm	200 mm	\varnothing 28 x 25 x 40 mm	2
108-44	108-05	\varnothing 28 mm	\varnothing 25 mm	200 mm		2
108-45	108-30	\varnothing 33 mm	\varnothing 30 mm	200 mm		2



108-39



108-45

Bow Thrusters



Boegschroeven - Querstrahlruder - Propulseurs d'étrave



108-30

108-30

Bow thruster with 2 brass 3 blade propellers.
 A G-ring ensures water tightness.
 The gears are water-lubricated.
 Diameter of the jet nozzle: \varnothing 30 x 33mm.
 Blue RM-410 7.2 Volt - 11 Amp max. (See page 16: art. 109-41)
 Length of the motor housing: 48 mm.
 Total length: 138 mm.
 Total height: 85 mm.
 Weight 150 gr.



Optional motors
 6V code 109-40
 12V code 109-43
 see page 16

Optional 5 blade propeller
 108-38 see below



108-33




108-33 - 3 blade

METRIC shaft connection
 side screw M3 x 4mm included

Code	D mm	D inch	R/L	shaft hole	pitch mm	Hub \varnothing x Length	RPM max.
108-33	29	1.14	R	\varnothing 4 mm	26,7	12 x 9mm	14500

108-38



108-38

METRIC shaft connection
 side screw M3 x 4mm included

Optional 5 blade propeller


Code	D mm	D inch	R/L	shaft hole	pitch mm	Hub \varnothing x Length	RPM max.
108-38	29	1.14	R	\varnothing 4 mm	26,7	12 x 9mm	14500

Rudders

Roeren - Ruder - Gouvernails

Code

- Balance rudders for electric boats and scale models with realistic blade shapes.**
- 107-00: Blade size 25x42 mm (ABS), shaft \varnothing 3 mm brass, nylon tiller arm and ABS tube.
 - 107-01: The same construction, blade size > 30x49 mm.
 - 107-02: For the bigger scale Model \varnothing 4 mm stainless steel shaft and hard brass bearings. Tiller arm with a non slip connection (26 splines). Blade size: 36x60 mm.
 - 107-04: Slanting rudder for the competition boats, to make sharp corners. Shaft 5mm SS, tube > brass and hard brass bearings.
 - 107-05: Rudder construction for general use.
 - 107-06: Rudder construction for general use.
- Balance rudders for speedboats up to 3,5 cc.**
- 107-30: Blade 22x40mm,
 - 107-31: 35x47mm SS Shaft and hard brass bearings
- 107-38/39/40/41/43: Nylon Tiller arms with 26 splines and \varnothing 2-3-4-5-6 mm hole. See page 23.
- 107-42: Nylon Tiller arm for rudder with \varnothing 3 mm shaft. See page 23.



See page 26.


Propeller Shafts

Schroefassen - Schiffswellen - Arbres d'hélices



Code	Max RPM In the water	Tube diameter C	Bearing front	Bearing rear	Tube length A	Shaft length B	D	Thread x Length E	G
300-00	12000	Ø 5x6 mm	Bronze	Hard Brass	140 mm	180 mm	Ø 2 mm	M2 x 10 mm	
300-01	7000	Ø 5x7 mm	Hard Brass	Hard Brass	220 mm	270 mm	Ø 4 mm	M4 x 16 mm	
300-03	10000	Ø 4,5x8 mm	Bronze	Bronze	220 mm	290 mm	Ø 4 mm	M4 x 18 mm	Ø 10,20 mm
300-04	9000	Ø 5x6 mm	Bronze	Hard Brass	228 mm	270 mm	Ø 3 mm	M3 x 11 mm	Ø 08,70 mm
300-11	16000	Ø 8x10 mm	Ball Bearing	Bronze	370 mm	450 mm	Ø 6 mm	M5 x 25 mm	Ø 15,70 mm

These RABOESCH high quality propeller shafts have a large range of application. For simple electric boats which are made from ABS, wood, please use 300-00/04. 300-01-03 have strong ABS tubes which makes gluing to your scale model very simple. The other propeller shafts have brass tubes. 300-11 has an extra strong shaft and tube. All the RABOESCH propeller shafts can be shortened very easily. All shafts are made of STAINLESS STEEL.




You can shorten these shafts yourself by using a saw.

Code	A	B	C	D	E	G	Max PPM
301-00	240 mm	290 mm	Ø 8 mm	Ø 4 mm	M4	Ø 10,40 mm	10.000
301-01	240 mm	290 mm	Ø 6 mm	Ø 4 mm	M4	Ø 10,40 mm	10.000



Totally maintenance-free shaft and watertight propeller shafts. Bearing House (G) has a bronze bearing and a G/O-ring. Sleeves: Brass. Shafts: S.S. Precision nut: (F). Rear Bearing: Delrin. Maximum RPM: 15.000 in the water.

These shafts are suitable for sailing ships with auxiliary motor and classic small steam boats.




Code	A	B	C	D	E	G	Max RPM
301-22	150 mm	186 mm	Ø 6 mm	Ø 4 mm	M4 x16 mm	Ø 10,50 mm	10.000
301-23	175 mm	211 mm	Ø 6 mm	Ø 4 mm	M4 x16 mm	Ø 10,50 mm	10.000
301-24	200 mm	236 mm	Ø 6 mm	Ø 4 mm	M4 x16 mm	Ø 10,50 mm	10.000
301-25	225 mm	261 mm	Ø 6 mm	Ø 4 mm	M4 x16 mm	Ø 10,50 mm	10.000
301-26	254 mm	290 mm	Ø 6 mm	Ø 4 mm	M4 x16 mm	Ø 10,50 mm	10.000



Totally maintenance-free shaft and watertight propeller shafts. Bearing House (G) has a bronze bearing and a G/O-ring. Sleeves: Brass. Shafts: S.S. Precision nut: (F). Rear Bearing: Delrin. Maximum RPM: 15.000 in the water.

These shafts are suitable for sailing ships with auxiliary motor and classic small steam boats.



Propeller Shafts

Schroefassen - Schiffswellen - Arbres d'hélices




Code	A	B	C	D	E	G	RPM
301-07	240 mm	290 mm	Ø 8 mm	Ø 4 mm	M4	Ø 15,80 mm	15.000
301-08	240 mm	290 mm	Ø 8 mm	Ø 5 mm	M5	Ø 15,80 mm	15.000
301-09	395 mm	450 mm	Ø 8 mm	Ø 4 mm	M4	Ø 15,80 mm	15.000
301-10	395 mm	450 mm	Ø 10 mm	Ø 5 mm	M5	Ø 15,80 mm	15.000

301-07 > 10



Totally maintenance-free shaft and watertight propeller shafts. Bearing House (G) has a ball bearing and a G-ring. Sleeves: Brass. Shafts: S.S. Precision nut: (F). Rear Bearing: Delrin. Maximum RPM: 15.000 in the water.




You can shorten these shafts yourself by using a saw.

Code	A	B	C	D	E	G	H	S
301-11	140 mm	230 mm	Ø 6 mm	Ø 2 mm	M2		P-Bracket 301-14	Ø 2 mm O ring
301-12	148 mm	270 mm	Ø 6 mm	Ø 3 mm	M3	Ø 08,70 mm	P-Bracket 301-15	Ø 3 mm O ring
301-13	153 mm	330 mm	Ø 8 mm	Ø 4 mm	M4	Ø 10,40 mm	P-Bracket 301-16	Ø 4 mm G ring
301-18	163 mm	390 mm	Ø 8 mm	Ø 5 mm	M5	Ø 10,40 mm	P-Bracket 301-17	Ø 5 mm O ring

301-11 > 18



Totally maintenance-free shaft and watertight propeller shafts. Bearing House (G) has a bronze bearing and a G/O-ring. Sleeves: Brass. Shafts: S.S. Precision nut: (F). Rear Bearing: Delrin. Maximum RPM: 15.000 in the water.



You can shorten these shafts yourself by using a saw.

Code	Length	Diam	Thread x Length	Stainless steel METRIC shaft
350-59	230 mm	Ø 2 mm	M2 x 10 mm	350-59-60-62-64-69-70
350-60	270 mm	Ø 3 mm	M3 x 11 mm	
350-61	290 mm	Ø 4 mm	M3 x 11 mm	350-61-63-65-66
350-62	290 mm	Ø 4 mm	M4 x 18 mm	
350-63	290 mm	Ø 5 mm	M4 x 18 mm	
350-64	450 mm	Ø 5 mm	M5 x 25 mm	
350-65	450 mm	Ø 6 mm	M4 x 25 mm	
350-66	450 mm	Ø 6 mm	M5 x 25 mm	
350-69	450 mm	Ø 4 mm	M4 x 23 mm	
350-70	290 mm	Ø 5 mm	M5 x 18 mm	

You can shorten these shafts yourself by using a saw.

These RABOESCH high quality propeller shafts have a large range of application.

350-59 > 70



Couplings

Koppelingen - Kupplungen - Cardans

106-40 + 2x insert 106 serie



106-40 Cardan coupling

Code	length	description
106-40	32 mm	Nylon Coupling



106-20 > 25 Insert

Code	Shaft or Engine Connection
106-20	M4
106-21	M5
106-22	M6
106-23	1/4 inch UNF
106-24	1/4 inch BSF
106-25	3/16 inch UNF



106-54 > 58 Rigid Couplings 2x Metric lock screw included

Code	Mounting hole	Length	Outer dimensions
106-54	Ø 2,0 mm	15 mm	Ø 10,0 mm
106-55	Ø 3,0 mm	20 mm	Ø 11,0 mm
106-56	Ø 4,0 mm	25 mm	Ø 12,0 mm
106-57	Ø 5,0 mm	25 mm	Ø 13,0 mm
106-58	Ø 6,0 mm	30 mm	Ø 13,0 mm



106-30 Double insert

Code	D mm/inch	Shaft or Engine Connection
106-30		Double insert



106-59 > 67 Rigid Couplings for different shaft connections 2x Metric lock screw included

Code	Mounting hole	Length	Outer dimensions
106-59	Ø 3,0 > 2,3 mm	20 mm	Ø 11,0 mm
106-60	Ø 4,0 > 2,3 mm	25 mm	Ø 12,0 mm
106-61	Ø 3,2 > 3,0 mm	20 mm	Ø 11,0 mm
106-62	Ø 4,0 > 3,0 mm	25 mm	Ø 12,0 mm
106-63	Ø 4,0 > 3,2 mm	25 mm	Ø 12,0 mm
106-64	Ø 5,0 > 4,0 mm	25 mm	Ø 13,0 mm
106-65	Ø 6,0 > 4,0 mm	30 mm	Ø 13,0 mm
106-66	Ø 5,0 > 3,2 mm	25 mm	Ø 13,0 mm
106-67	Ø 6,0 > 5,0 mm	30 mm	Ø 13,0 mm



106-02 > 13 Insert

Code	Shaft or Engine Connection
106-02	Ø 2,0 mm
106-03	Ø 2,3 mm
106-13	Ø 2,5 mm
106-04	Ø 3,0 mm
106-05	Ø 4,0 mm
106-07	Ø 5,0 mm
106-08	Ø 6,0 mm
106-09	Ø 1/8 inch (3,18)
106-10	Ø 3/32 inch (2,38)
106-11	Ø 3/16 inch (4,76)
106-12	Ø 1/4 inch (6,35)



101 + 102 + 2x insert 106 serie



101 / 102 male/female Coupling

Code		length	description
101-01	male	29 mm	Nylon Coupling
102-01	female	24 mm	Nylon Coupling



Spare Parts

Reserve onderdelen - Ersatzteile - Pièces de rechange



108-07		108-23		108-34		108-38 optional 5 blade for 108-30													
Loose jet nozzle		Loose jet nozzle		Gear set															
Code	description	Code	description	Code	description	Code	D mm	D inch	R/L	shaft mm	pitch mm								
108-07	for bow thruster 108-01	Ø 14 x 16 mm	108-23	for bow thruster 108-20	Ø 10 x 12 mm	108-34	for bow thruster 108-30					108-38	29		R	Ø 4	26,7		
108-08		108-32		108-35		354-01 > 02 Stainless steel bolts													
Loose jet nozzle		Loose jet nozzle		Paddle set															
Code	description	Code	description	Code	description	Code	description	D mm											
108-08	for bow thruster 108-02	Ø 16 x 19 mm	108-32	for bow thruster 108-30	Ø 30 x 33 mm	108-35	for bow thruster 108-01 > 03				354-01	stainless steel bolts (4x)	M2 x 6mm						
108-09		108-06		108-37		355-01 Parker													
Loose jet nozzle		Repair set		Paddle															
Code	description	Code	description	Code	description	Code	description	D mm											
108-09	for bow thruster 108-03	Ø 19 x 22 mm	108-06	for bow thruster 108-01 > 05		108-37	for bow thruster 108-20				355-01	parker (4x)	3 x 6mm						
108-10		108-21		108-36		359-01 > 05 G-Rings													
Loose jet nozzle		Repair set		Paddle set															
Code	description	Code	description	Code	description	Code	description	Dimension inside x outside x height											
108-10	for bow thruster 108-04	Ø 22 x 25 mm	108-21	for bow thruster 108-20		108-36	for bow thruster 108-04 > 05				359-01	G-rings (2x)	Ø 3 x Ø 6 x 3,0mm						
108-11		108-31		108-33		104-46 Rubber O-Rings													
Loose jet nozzle		Repair set		Brass propeller for bow thruster 108-30															
Code	description	Code	description	Code	D mm	D inch	R/L	shaft mm	pitch mm	Code	description	Dimension inside x outside x height							
108-11	for bow thruster 108-05	Ø 25 x 28 mm	108-31	for bow thruster 108-30	108-33	29		R	Ø 4	26,7	104-41	for shaft 2mm (2x)	Ø 2 x Ø 5 x 1,5mm						

Spare Parts

Reserve onderdelen - Ersatzteile - Pièces de rechange



100-01 Hose nipple		
Code	description	D mm
100-01	hose nipple for hull	4 mm

301-14 > 17 P-Bracket		
Code	description	D mm
301-14	single p-bracket with brass bearing	Ø 2 mm
301-15	single p-bracket with brass bearing	Ø 3 mm
301-16	single p-bracket with brass bearing	Ø 4 mm
301-17	single p-bracket with brass bearing	Ø 5 mm

356-01 Brass nipple		
Code	description	D mm
356-01	brass nipple (4x)	M4 x 17 x Ø 6

360-01 > 10 Delrin Bearings			
Code	inside x outside x height	for shaft	Content
360-01	Ø 4 x Ø 5 x 8mm	301-01 > 06	2
360-07	Ø 4 x Ø 7 x 10mm	301-00/07/09/13	2
360-08	Ø 5 x Ø 7 x 10mm	301-08	2
360-10	Ø 5 x Ø 8 x 10mm	301-10	2

351-01 > 04 Brass nuts plus washer		
Code	description	D mm
351-01	brass nuts plus washers (4x)	M2
351-02	brass nuts plus washers (4x)	M3
351-03	brass nuts plus washers (4x)	M4
351-04	brass nuts plus washers (4x)	M5

358-00 > 04 Bronze bearings		
Code	description	Dimension inside x outside x height
358-00	bronze bearings (2x)	Ø 2 x Ø 5 x 3mm
358-01	bronze bearings (2x)	Ø 3 x Ø 6 x 6mm
358-02	bronze bearings (2x)	Ø 4 x Ø 8 x 8mm
358-03	bronze bearings (2x)	Ø 5 x Ø 8 x 8mm
358-04	bronze bearings (2x)	Ø 6 x Ø 10 x 12mm

106 / 352 Hexagon key and setscrews		
Code	description	D mm
106-71	hexagon key 1,5 mm for M3	
106-72	hexagon key 1,27 mm for M2,5	
352-01	hexagon key + 4x set screw	M3 x 4 mm
352-02	hexagon key + 4x set screw	M4 x 4 mm
352-03	hexagon key + 4x set screw	M5 x 4 mm
352-00	hexagon key + 4x set screw	M2,5 x 3 mm

107-39 > 42 Tiller arms			
Code	description	D mm	Content
107-38	Nylon Tiller arm	2 mm	1
107-39	Nylon Tiller arm	3 mm	1
107-40	Nylon Tiller arm	4 mm	1
107-41	Nylon Tiller arm	5 mm	1
107-42	Nylon Tiller arms	3 mm	2
107-43	Nylon Tiller arm	6 mm	1

353-01 > 04 Stainless steel		
Code	description	D mm
353-01	stainless steel nuts plus washers (4x)	M2
353-02	stainless steel nuts plus washers (4x)	M3
353-03	stainless steel nuts plus washers (4x)	M4
353-04	stainless steel nuts plus washers (4x)	M5

357-01 > 03 Ball bearings		
Code	description	Dimension inside x outside x height
357-01	ball bearings (2x)	Ø 4 x Ø 13 x 5mm
357-02	ball bearings (2x)	Ø 5 x Ø 13 x 4mm
357-03	ball bearings (2x)	Ø 6 x Ø 13 x 5mm

300 High Temperature Shaft Grease		
Shaft grease - Schroeffassenvet - Schiffswellen fett - Lubrification Arbres d'hélices		
Code	description	Weight
300-70	High Temperature Shaft Grease	500 gram

104-03 > 09 Rubber vibration absorbers					
Code	description	Ø x H mm	thread	° shore	content
104-03	Vibr. Absorbers	Ø 10 x 10 mm	M4 x 10	70°	4x
104-04	Vibr. Absorbers	Ø 15 x 8 mm	M4 x 10	70°	4x
104-05	Vibr. Absorbers	Ø 15 x 12 mm	M4 x 10	70°	4x
104-09	Vibr. Absorbers	Ø 20 x 15mm	M6 x 18	70°	4x

Glue advice

Lijmadvies - Empfehlung zum Kleben - Conseils de collage

- GB** Our plastic products are produced from the polymer ASA (Acrylonitrile - Styrene - Acrylester) and Styrene. They can simply be glued by using hard plastic PVC-glue or with two component glue. On this page we give you glue advice.
- NL** Onze kunststof producten zijn vervaardigd van het polymeer: ASA (Acrylonitrile - Styreen - Acrylester) en Styreen. Ze kunnen eenvoudig worden verlijmd met hardplastic PVC-lijm of 2-componentenlijm. Op deze pagina geven wij u lijmadvies.
- DE** Unsere Kunststoffprodukte sind aus Polymer ASA (Acrylonitril - Styrol - Acrylester) hergestellt und aus Styrol und können einfach mit dem Hartplastik-PVC-Klebstoff oder mit einem Zwei-Komponenten-Klebstoff verklebt werden. Auf dieser Seite geben wir Ihnen Kleber Beratung.
- FR** Nos produits en plastique sont réalisés en polymère ASA (acrylonitrile styrène acrylate) et en styrène. Ils sont faciles à coller avec une colle pour PVC rigide ou une colle à deux composants. Sur cette page, nous vous donnons des conseils de colle.



Plastic glue for ASA, Styrene, PVC, Polycarbonate and PVC foam



UHU plast special UH45880
www.uhu-profishop.com



BISON Model Plastic
www.bison.nl
www.bison.be



RUDERER L530
www.ruderer.de



Deluxe Roket Plastic Glue AD62
www.deluxematerials.com



Faller Expert 170492
Faller Super Expert 170490
www.faller.de



Two component glue and instant adhesive for Evacast, Polyester, Polypropylene, Lexan and Brass



Pattex Power Epoxy 2 component glue
www.pattex.com



LOCTITE 401 instant adhesive
www.loctite.com



Rubber glue



BISON Rubber Glue
www.bison.nl
www.bison.be



Pattex Special Rubber Glue
www.pattex.com



Deluxe Roket Cyano Glue Gel AD69
www.deluxematerials.com

Plastic profiles & sheets

Kunststof profielen & platen - Kunststoff Profile & Platten - Profilés & feuilles en Plastique



GB

Raboesch Models BV is also a plastic sheets & profiles manufacturer. Since January 2015 we have been providing these products under a new trading name: MAQUETT. Our high-quality products are used for scale model construction, model building and model railway building. We furthermore also provide our products to the furniture sector, architectural firms, research & development departments and the general industry.

Ask your local model building shop or hobby shop for the MAQUETT catalog or download the catalog via www.maquett.nl. On our website you will also find an up-to-date overview of our products and activities.

NL

Raboesch Models BV is tevens fabrikant van plastic sheets & profiles. Sinds januari 2015 leveren we deze producten onder de nieuwe handelsnaam MAQUETT. Onze kwalitatief hoge producten worden gebruikt voor schaalmodelbouw, maquettebouw en modelspoorbouw. Daarnaast leveren we aan de meubel branche, architectenbureaus, research & development afdelingen en de industrie.

Vraag uw lokale modelbouwwinkel naar de MAQUETT catalogus of download de catalogus op www.maquett.nl. Op onze website treft u tevens een actueel overzicht aan van onze producten en activiteiten.

DE



Raboesch Models BV ist auch Hersteller von Kunststoffplatten und Profilen. Ab Januar 2015 liefern wir dies Produkte unter dem neuen Handelsnamen MAQUETT. Unsere qualitativ hochwertigen Produkte werden für maßstabgerechten Modellbau, Maquettenbau und den Bau von Modelleisenbahnen eingesetzt. Darüber hinaus beliefern wir die Möbelindustrie, Architekturbüros, sowie die Forschungs- und Entwicklungsabteilungen und die Industrie.

Fragen Sie in Ihrem Modellbauladen vor Ort nach dem MAQUETT Katalog oder laden Sie den Katalog auf www.maquett.nl herunter. Auf unserer Website finden Sie ebenfalls eine aktuelle Übersicht unserer Produkte und Aktivitäten

FR

Raboesch Models BV est aussi un fabricant de feuilles de plastique et de profilés. A partir du mois de Janvier 2015, nous fournirons ces produits sous le nouveau nom commercial de MAQUETT. Nos produits de haute qualité sont utilisés pour la construction de maquettes, la construction de modèles et la construction dans le cadre du modélisme ferroviaire. Nous livrons également à l'industrie du meuble, aux cabinets d'architectes, aux départements de recherche et développement et à l'industrie.

Demandez à votre magasin de construction de modèles local le catalogue MAQUETT ou téléchargez le catalogue sur www.maquett.nl. Sur notre site web, vous trouverez également un aperçu actuel de nos produits ainsi que de nos activités.



X-LARGE

328x997 mm / 12,9x39,3 inch

part. nr. color mm content

Styrene

701-04	White	1,00	1
701-05	White	1,50	1
701-06	White	2,00	1

PVC foam

705-01	White	2,00	1
705-02	White	3,00	1





hobby products

www.raboeschmodels.com



Like us on facebook
facebook.com/raboeschmodels

Made in the Netherlands



Raboesch Models BV • Schepenveld 18 • NL-3891 ZK Zeewolde cvzThe Netherlands